



# High Wall Cooling only

DFM/DFO 520 to 570 BG

A complete range from 2.0 kW to 7.0 kW



## Features

- Maximum energy efficiency: Class "A"
- Ultra silent
- Ecological R410A refrigerant
- Includes triple BIO filter for dust, bacteria and odours
- Reduced dimensions
- Preinstallation kit included
- High efficiency rotary compressors



## Remote controller

- Wireless
- 5 operation modes (Cool/Heat/Auto/Dry/Fan)
- Sleep mode
- Room temperature setting
- Fan speed selection
- Timer setting function
- Air flow direction setting
- LCD display



# High Wall Cooling only

## DFM/DFO 520 to 570 BG



### Technical features

Indoor unit		Sizes	DFM-520 BG	DFM-527 BG	DFM-535 BG	DFM-540 BG	DFM-560 BG	DFM-570 BG
Outdoor unit		Sizes	DFO-520 BG	DFO-527 BG	DFO-535 BG	DFO-540 BG	DFO-560 BG	DFO-570 BG
Cooling capacity		kW	2.0	2.5	3.5	4.5	6.0	7.0
Cooling capacity		Kcal/h	1 720	2 150	3 010	3 870	5 160	6 020
Compressor		Type	Rotary					
Refrigerant			R410A					
Power supply		V/Ph/Hz	230 / 1 / 50 + E					
Power input		kW	0.62	0.77	1.05	1.40	1.85	2.60
EER			3.23	3.25	3.33	3.21	3.24	2.69
Indoor airflow		m <sup>3</sup> /h	400	500	620	620	720	1 200
Sound pressure	Indoor	dB(A)	28	30	34	37	39	41
	Outdoor	dB(A)	42	43	44	48	51	50
Dimensions	Indoor	H (mm)	250	250	285	285	290	326
		W (mm)	770	770	830	830	907	1 180
		D (mm)	180	180	189	189	195	227
	Outdoor	H (mm)	430	540	540	540	710	1 006
		W (mm)	660	848	848	848	950	847
		D (mm)	260	320	320	320	410	420
Net weight	Indoor unit	kg	8.5	8.5	11	11	12	18
	Outdoor unit	kg	32	38	40	40	59	72
Piping	Type of connection		Flare					
	Diameter	Gas	3/8"	3/8"	1/2"	1/2"	5/8"	5/8"
		Liquid	1/4"	1/4"	1/4"	1/4"	3/8"	3/8"

Nominal cooling capacity based on : - Indoor Air Temp. 27°C DB / 19°C WB - Outdoor Air Temp. 35°C DB

Nominal heating capacity based on : - Indoor Air Temp. 21°C DB - Outdoor Air Temp. 7°C DB/6°C WB

Piping length : 5 m with initial charge